

**Double V-Belts**

Profil Section CC/HCC

Bezugslänge Reference length (mm)	Riemen-Nr. Belt no.	EUR Stück each
2280	CC 86	auf Anfrage on request
2500	CC 94	
2800	CC 106	
3200	CC 122	
3310	CC 126	
3765	CC 144	
4000	CC 153	
4216	CC 162	
4300	CC 165	
4500	CC 173	
5000	CC 193	
5300	CC 204	
5340	CC 206	
5750	CC 224	

Profil Section DD/HDD

Bezugslänge Reference length (mm)	Riemen-Nr. Belt no.	EUR Stück each

Gewicht Belt weight: $\approx 0,440$ kg/m

Profil Section 22 x 22

Bezugslänge Reference length (mm)	Riemen-Nr. Belt no.	EUR Stück each
5180	22	auf Anfrage on request
5220	22	
5850	22	
6270	22	

Profil Section 25 x 22

Bezugslänge Reference length (mm)	Riemen-Nr. Belt no.	EUR Stück each
auf Anfrage on request		

Zwischenlängen und Sonderausführungen ab:
 Profil CC/HCC 2000 bis 19 500 mm
 Profil 22 x 22 auf Anfrage

Umrechnungswerte von der Riemen-Nr. zur Bezugslänge:

Profil CC/HCC bis Riemen-Nr. 210
 Riemen-Nr. $\times 25,4 = \text{mm} + 107 \text{ mm}$
 über Riemen-Nr. 210
 Riemen-Nr. $\times 25,4 = \text{mm} + 56 \text{ mm}$

Profil DD/HDD bis Riemen-Nr. 210
 Riemen-Nr. $\times 25,4 = \text{mm} + 132 \text{ mm}$
 über Riemen-Nr. 210
 Riemen-Nr. $\times 25,4 = \text{mm} + 69 \text{ mm}$

Non standard lengths available:
 Section CC/HCC 2000 up to 19 500 mm
 Section 22 x 22 on request

To convert from belt no. (that is theoretical inside length in inches) to reference length:

Section CC/HCC up to belt no. 210
 belt no. $\times 25.4 = \text{mm} + 107 \text{ mm}$
 over belt no. 210
 belt no. $\times 25.4 = \text{mm} + 56 \text{ mm}$

Section DD/HDD up to belt no. 210
 belt no. $\times 25.4 = \text{mm} + 132 \text{ mm}$
 over belt no. 210
 belt no. $\times 25.4 = \text{mm} + 69 \text{ mm}$

Weitere Abmessungen auf Anfrage. Further sizes on request.