



DATA SHEET CONVEYOR BELT



Article-No.	410150
Product name	2E/PW22
Category	STABILOFLEX
Product group	PU Conveyor Belt

SPECIFICATIONS

Tractin layer

Material	polyester fabric
Number of layers	2
Properties	lateral stabil

Top side

Coating material	PU
Color	white
Thickness (mm)	0,2
Surface	smooth, adhesive
Hardness (Shore A)	

Bottom side

Coating material	PU
Color	white
Thickness (mm)	0,2
Surface	smooth

TECHNICAL DATA

Total thickness (mm)	1,5
Weight (kg/qm)	1,7
Temperature longtime (°C)	- 20 / + 100
Temperature shorttime (°C)	
Friction coefficient (steel)	0,40

Tensile strength (1% tension) (N/mm)	7
---	---

Breaking strength (N/mm)	
--------------------------	--

Minimum pulley Ø (mm)	25
with bending Ø (mm)	35

Max. production width (mm)	2000
----------------------------	------

Last modification on	05.16.2013
----------------------	------------



PROPERTIES

Food contact suitability

EU 10/2011	✓
FDA	✓
USDA	keine Angabe

Antistatic	✓
Metal detector suitable	✓
Oil & fat resistant	✓
Flame resistant	Nein/no
Smooth running fabric	---

Suitable for

Slider bed	bedingt
Rollers	✓
Trough	Nein/no
Curved	Nein/no

Divers

for small pulley diameters, abrasion resistant, abrasion resistant edges

Applications

Food industry, convenience food, process belt

Products

Meat, Poultry, Ready Meals, Animal Feed, Dairy Products, Convenience