



DATA SHEET CONVEYOR BELT



Article-No.	413938
Product name	2E/SW00 HT
Category	RAPID
Product group	Silicone Conveyor Belt

SPECIFICATIONS

Tractin layer

Material	polyester fabric
Number of layers	2
Properties	lateral stabil

Top side

Coating material	Silikone
Color	white
Thickness (mm)	0,0
Surface	
Hardness (Shore A)	

Bottom side

Coating material	fabric
Color	white
Thickness (mm)	0,0
Surface	fabric impregnated

TECHNICAL DATA

Total thickness (mm)	1,3
Weight (kg/qm)	1,2
Temperature longtime (°C)	- 40 / + 180
Temperature shorttime (°C)	
Friction coefficient (steel)	0,15

Tensile strength (1% tension) (N/mm)	4
Breaking strength (N/mm)	120

Minimum pulley Ø (mm)	40
with bending Ø (mm)	40

Max. production width (mm)	2000
----------------------------	------

Last modification on	01.01.2016
----------------------	------------

PROPERTIES

Food contact suitability

EU 10/2011	✓
FDA	✓
USDA	N/A

Antistatic	✓
Metal detector suitable	n.g.
Oil & fat resistant	✓
Flame resistant	Nein/no
Smooth running fabric	✓

Suitable for

Slider bed	✓
Rollers	✓
Trough	Nein/no
Curved	Nein/no

Divers

heat-resistant

Applications

Food industry, packaging, process belt, packaging belt, transfer belt, ovens, drying tunnel, weighing belt

Products

Baked goods (biscuits), Sweets, Chocolate / confectionery, Frozen foods, Hygiene, Poultry, Food packaging, Ready meals, Meat