



DATA SHEET CONVEYOR BELT



Article-No.	40319
Product name	2E/VS05 M
Category	UNITRANS
Product group	PVC Conveyor Belt

SPECIFICATIONS

Tractin layer

Material	polyester fabric
Number of layers	2
Properties	lateral stabil

Top side

Coating material	PVC
Color	black
Thickness (mm)	0,4
Surface	matt
Hardness (Shore A)	90

Bottom side

Coating material	fabric
Color	nature
Thickness (mm)	0,0
Surface	fabric

TECHNICAL DATA

Total thickness (mm)	1,8
Weight (kg/qm)	2,1
Temperature longtime (°C)	- 10 / + 70
Temperature shorttime (°C)	- 15 / + 80
Friction coefficient (steel)	0,24

Tensile strength (1% tension) (N/mm)	8
Breaking strength (N/mm)	120

Minimum pulley Ø (mm)	20
with bending Ø (mm)	50

Max. production width (mm)	3000
----------------------------	------

Last modification on	01.10.2018
----------------------	------------



PROPERTIES

Food contact suitability

EU 10/2011	Nein/no
FDA	Nein/no
USDA	Nein/no

Antistatic	Nein/no
Metal detector suitable	keine Angabe
Oil & fat resistant	Nein/no
Flame resistant	Nein/no
Smooth running fabric	Nein/no

Suitable for

Slider bed	✓
Rollers	✓
Trough	Nein/no
Curved	Nein/no

Divers

good abrasion resistance, suitable for stagnation

Applications

Printing and paper, textiles, plastic production, sorting belt, fitness belt, inspection and camera belt, stagnation belt, supermarket checkout, accumulation belt

Products

letters, cardboard, packages, boxes, plastic, textile, paper, metal, sheet metal