



## DATA SHEET CONVEYOR BELT



<b>Article-No.</b>	<b>40315</b>
<b>Product name</b>	<b>2E/VW55</b>
Category	<b>UNITRANS</b>
Product group	PVC Conveyor Belt

### SPECIFICATIONS

#### Tractin layer

Material	polyester fabric
Number of layers	2
Properties	lateral stabil

#### Top side

Coating material	PVC
Color	white
Thickness (mm)	0,5
Surface	smooth, adhesive
Hardness (Shore A)	60

#### Bottom side

Coating material	PVC
Color	white
Thickness (mm)	0,5
Surface	structure

### TECHNICAL DATA

Total thickness (mm)	2,5
Weight (kg/qm)	2,7
Temperature longtime (°C)	- 15 / + 70
Temperature shorttime (°C)	
Friction coefficient (steel)	0,35 - 0,4

Tensile strength (1% tension) (N/mm)	8
Breaking strength (N/mm)	120

Minimum pulley Ø (mm)	60
with bending Ø (mm)	90

Max. production width (mm)	2000
----------------------------	------

Last modification on	01.01.2016
----------------------	------------

### PROPERTIES

#### Food contact suitability

EU 10/2011	✓
FDA	✓
USDA	keine Angabe

Antistatic	✓
Metal detector suitable	keine Angabe
Oil & fat resistant	✓
Flame resistant	Nein/no
Smooth running fabric	---

#### Suitable for

Slider bed	Nein/no
Rollers	✓
Trough	Nein/no
Curved	Nein/no

#### Divers

good abrasion resistance, adhesive

#### Applications

Food industry, packaging, process belt, agriculture

#### Products

Baked Snacks, Bakery Products (Biscuits, Bread), Chocolate / Confectionery, Convenience Food, Pastry, Food Packaging, Fruits, Vegetables, Fish, Seafood, Poultry, Meat